

INDUSTRIAL CABLE REEL IP42 - "SERIES 4000"




Technical features and cable length of these cable reels are similar to "XF Series". This "4000 Series" is equipped with fastening swivelling bracket, roller cable guide, feeding side terminal board and 10 Amp collector with double earth contact. Protection degree IP42. The ratchet stop device allows to stop from the cable reel the uncoiled cable partially or totally: it is useful if cable unwinding is manually made.

REMARKS: All cable reels are supplied with predisposition for cable-stop device SWITCHED ON. To turn off, it is enough to make a simple manoeuvre.

Optional items:

Art. 950 - Supplement for the variation of standard lengths on reels (**Must be added to the cable cost**). The variation is possible ONLY for large quantities.

Art. 949/804-4000 - Optional device to make the fastening bracket fixed instead of pivoting. Essential for ceiling installation and for 7 and 8 set-ups according to installation methods

Cond.	sez. cond. (mm ²)	cable length (m)	Article	KW		Ø cable (mm)	Prot. therm.	V max	Cable type		
											
1	6	15+1	4106			5,5	no		H05 V-F		
	16	10+1	4116			8	no		H05 V-F		
2	1	17+1	4210	230V	0,9	1,4	6,5	si	500	H05 VV-F	
		12+1	4210 RNF				8,5	si	750	H07 RN-F	
	1,5	15+1	4215			1,1	1,6	7,5	si	500	H05 VV-F
3	1,5	14+1	4315	230V	1,2	1,8	8,5	si	500	H05 VV-F	
		9+1	4315 RNF				10	si	750	H07 RN-F	
	2,5	9+1	4325			1,9	2,5	10	si	500	H05 VV-F
		7+1	4325 RNF					12	si	750	H07 RN-F
4	1,5	10+1	4415	400V	1,4	1,9	9,5	no	500	H05 VV-F	
		8+1	4415 RNF				11	no	750	H07 RN-F	
5	1,5	8+1	4515			1,4	1,9	10,5	no	500	H05 VV-F
		7+1	4515 RNF					12	no	750	H07 RN-F

Reel dimensions series 4000
