

INDUSTRIAL CABLE REEL IP42 - "SERIES 7000"




Technical features and cable length of these cable reels are similar to "PR Series", but with plastic outer casing. This new "7000 Series" is equipped with fastening swivelling bracket, roller cable guide, feeding side terminal board and 10 Amp amperage collector with double earth contact. Protection degree is IP42. The ratchet stop device allows to stop from the cable reel the uncoiled cable partially or totally: it is useful if cable unwinding is manually made.

REMARKS: All cable reels are supplied with predisposition for cable-stop device SWITCHED OFF. To set it, it is enough to make a simple manoeuvre.

Optional items:

Art. 950 - Supplement for the variation of standard lengths on reels (**Must be added to the cable cost**). The variation is possible **ONLY** for large quantities.

Art. 949/805-7000 - Optional device to make the fastening bracket fixed instead of pivoting. Essential for ceiling installation and for 7 and 8 set-ups according to installation methods.

Cond.	sec. cond. (mm ²)	cable length (m)	Article	KW		Ø cable (mm)	weight cable (gr/m)	Prot. therm.	V max	Cable type						
																
1	16	20+2	7116			8	180	no		H05 V-F						
2	1,5	25+2	7215	230V	1,1	230V	1,8	7,5	80	no	500	H05 VV-F				
3	1,5	25+2	7315		1,1		1,8	8,5	120	no	500	H05 VV-F				
		20+2	7315 RNF		1,1		1,8	10	130	no	750	H07 RN-F				
	2,5	20+2	7325		2,0		3,0	10	160	no	500	H05 VV-F				
		17+2	7325 RNF					12	170	no	750	H07 RN-F				
4	1,5	25+2	7415		400V		1,1	400V	1,8	9,5	145	no	500	H05 VV-F		
		16+2	7415 RNF	11		160				no	750	H07 RN-F				
	2,5	18+2	7425	2,0		3,0			11	205	no	500	H05 VV-F			
		13+2	7425 RNF						13	220	no	750	H07 RN-F			
5	1,5	20+2	7515	1,5		2,2			3,0	10,5	190	no	500	H05 VV-F		
		15+2	7515 RNF							12	200	no	750	H07 RN-F		
	2,5	15+2	7525							2,0	3,0	12,5	250	no	500	H05 VV-F
		10+2	7525 RNF									14	260	no	750	H07 RN-F

Reel dimensions series 7000
